

EVERISON INTERNATIONAL GROUP INC

Hydraulic Pneumatic Cylinder Pipe

- a) Grades: 20, 35, 45, 16Mn, 20CrMo, 42CrMo
- b) Standards: GB/T3939, GB 8713, ASTM A519, EN10305-1, DIN2391, GB 8713; also able to produce according to special arrangements that are requested by the buyer.
- c) High Machinery Accuracy:
 - a. Straightness 0.3-2.0mm/1000mm
 - b. Surface Roughness Ra3.2-0.45
 - c. Size accuracy IT9-14 level, inside surface is less than 0.1% of the nominal size roundness

SEE CHART ON NEXT PAGE

EVERISON INTERNATIONAL GROUP INC. (STEEL PIPES SPECIFICATION CHART)

DIA/THK	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	32	33	34	36	38	40	50			
28 (1.1)																																						
33 (1.29)																																						
38 (1.49)																																						
44 (1.73)																																						
50 (1.96)																																						
58 (2.28)																																						
63 (2.48)																																						
68 (2.67)																																						
76 (2.99)																																						
83 (3.26)																																						
89 (3.5)																																						
95 (3.74)																																						
98 (3.85)																																						
102 (4.01)																																						
105 (4.13)																																						
108 (4.25)																																						
113 (4.44)																																						
117 (4.60)																																						
121 (4.76)																																						
127 (5.00)																																						
133 (5.23)																																						
137 (5.39)																																						
140 (5.51)																																						
146 (5.74)																																						
152 (5.98)																																						
159 (6.25)																																						
168 (6.61)																																						
180 (7.08)																																						
194 (7.63)																																						
203 (7.99)																																						
219 (8.62)																																						
224 (8.81)																																						
232 (9.13)																																						
245 (9.64)																																						
252 (9.92)																																						
273 (10.74)																																						
299 (11.77)																																						
325 (12.79)																																						
351 (13.81)																																						
377 (14.84)																																						
402 (15.82)																																						
426 (16.77)																																						
450 (17.71)																																						
480 (18.89)																																						
500 (19.68)																																						
508 (20.00)																																						
530 (20.86)																																						